Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An optically pumped radiation-emitting semiconductor device having a semiconductor body, the semiconductor body comprising: which includes at least one pump radiation source (20) and

a surface-emitting quantum well structure; (11),

a pump radiation source constructed for generating a pump radiation for optically pumping the quantum well structure, the pump radiation source [[(20)]] and the quantum well structure [[(11)]] being in monolithically integrated form; [[,]] and the pump radiation source (20) generating pump radiation (2) for optically pumping the quantum well structure (11),

wherein a recess [[(10)]] for introducing the pump radiation [[(2)]] into the quantum well structure (11) is formed in the semiconductor body between the pump radiation source [[(20)]] and the quantum well structure [[(11)]].

wherein the pump radiation source is a pump laser comprising a resonator, and
wherein the quantum well structure is arranged within the resonator of the pump radiation
source.

2. (Currently Amended) The semiconductor device as claimed in claim 1, wherein the recess [[(10)]] is in <u>a</u> trench form and runs obliquely or perpendicular with respect to a direction of propagation of the pump radiation [[(2)]].

- 3. (Currently Amended) The semiconductor device as claimed in claim 1, wherein the recess [[(10)]] has a first side face [[(26)]] facing the pump radiation source [[(20)]] and an opposite, second side face [[(27)]] facing the quantum well structure [[(11)]], the pump radiation [[(2)]] entering the recess [[(10)]] through the first side face [[(26)]] and then entering the quantum well structure [[(11)]] through the second side face [[(27)]].
- 4. (Currently Amended) The semiconductor device as claimed in claim 3, wherein the second side face [[(27)]] is parallel to the first side face [[(26)]].
- 5. (Currently Amended) The semiconductor device as claimed in claim 3, wherein <u>at</u> <u>least one of</u> the first <u>and/or</u> <u>and</u> the second side <u>face (26, 27)</u> <u>faces</u> includes an angle equal to [[the]] <u>a</u> Brewster angle with a direction of propagation of the pump radiation (2), in particular with a main direction of emission of the pump radiation source (20).
- 6. (Currently Amended) The semiconductor device as claimed in claim 1, wherein the recess [[(10)]] is filled with a dielectric or a semiconductor material.
- 7. (Currently Amended) The semiconductor device as claimed in claim [[6]] 1, wherein the recess [[(10)]] is filled with a material which has a refractive index substantially equal to [[the]] a refractive index of the pump radiation source [[(2)]], [[the]] a refractive index of the quantum well structure [[(11)]] or [[the]] a geometric mean of the latter two refractive indices.

- 8. (Currently Amended) The semiconductor device as claimed in claim 1, wherein the semiconductor device comprises a vertical emitter with a radiation-generating region formed by the quantum well structure [[(11)]].
- 9. (Currently Amended) The semiconductor device as claimed in claim 8, wherein the vertical emitter is a vertically emitting laser, in particular a VCSEL or a disc laser.

Claim 10 (Cancelled).

- 11. (Currently Amended) The semiconductor device as claimed in claim [[10]] $\underline{1}$, wherein the pump laser is an edge-emitting laser.
- 12. (Currently Amended) The semiconductor device as claimed in claim [[10]] $\underline{1}$, wherein the pump laser is a ring laser.

Claim 13 (Cancelled).

- 14. (Currently Amended) The semiconductor device as claimed in claim 1, wherein the pump radiation [[(2)]] is introduced into the quantum well structure (11) in the in a lateral direction.
- 15. (Currently Amended) The semiconductor device as claimed in claim 1, wherein the pump radiation source [[(20)]] and the surface-emitting quantum well structure [[(11)]] are formed from different semiconductor layer sequences.

- 16. (Currently Amended) The semiconductor device as claimed in claim 1, wherein the pump radiation source [[(20)]] and the surface-emitting quantum well structure [[(11)]] are formed epitaxially and in succession.
- 17. (Currently Amended) The semiconductor device as claimed in claim 1, wherein the recess [[(10)]] is arranged in a grow-in region between the pump radiation source [[(20)]] and the surface-emitting quantum well structure [[(11)]].
- 18. (Currently Amended) The semiconductor device as claimed in claim 1, wherein in that the pump radiation source [[(20)]] has at least one waveguide layer (23, 24).
- 19. (Currently Amended) A method for fabricating an optically pumped semiconductor device having a semiconductor body which includes a surface-emitting quantum well structure [[(11)]] and at least one pump radiation source [[(20)]] which generates pump radiation [[(2)]] for optically pumping the quantum well structure [[(11)]], the pump radiation source [[(2)]] and the quantum well structure [[(11)]] being monolithically integrated, the method comprising the steps of:
 - a) providing a substrate [[(1)]],
- b) epitaxially growing a plurality of semiconductor layers on to onto the substrate [[(1)]], which layers include the quantum well structure [[(11)]],
 - c) partially removing the semiconductor layers, [[and]]

- d) epitaxially growing the pump radiation source [[(20)]] in the region uncovered by the removal in step c) so that the pump radiation source [[(20)]] adjoins the quantum well structure [[(11)]], and
- <u>e)</u> <u>forming wherein</u> a recess [[(10)]] for introducing the pump radiation [[(2)]] into the quantum well structure, the recess being located (11) is formed between the pump radiation source [[(20)]] and the quantum well structure [[(11)]],

wherein the pump radiation source is a pump laser comprising a resonator, and
wherein the quantum well structure is arranged within the resonator of the pump radiation
source.

- 20. (Currently Amended) The method as claimed in claim 19, wherein [[in]] step d) further comprises growing semiconductor layers are grown in order to form the pump radiation source [[(20)]], these semiconductor layers in a grow-in region [[(19)]], being at least partially growing grown together in [[the]] a lateral direction with the quantum well structure [[(11)]], and wherein step e) further comprises forming the recess (10) is formed by at least partial removal of the grow-in region [[(19)]].
- 21. (Currently Amended) The method as claimed in claim 19, wherein the recess [[(10)]] is formed by etching, in particular, wet chemical or dry chemical etching.
- 22. (Currently Amended) The method as claimed in claim 19, wherein the recess [[(10)]] is designed in a trench form, in particular as an etched trench.

- 23. (Currently Amended) The method as claimed in claim 19, wherein the recess [[(10)]] is filled with a material which transmits the pump radiation.
- 24. (Currently Amended) The method as claimed in claim 23, wherein the recess [[(10)]] is filled with \underline{a} silicone or a semiconductor material.
- 25. (Currently Amended) A method for fabricating an optically pumped semiconductor device having a semiconductor body which includes a surface-emitting quantum well structure [[(11)]] and at least one pump radiation source [[(20)]] which generates pump radiation [[(2)]] for optically pumping the quantum well structure [[(11)]], the pump radiation source [[(2)]] and the quantum well structure [[(11)]] being monolithically integrated, the method comprising the steps of:
 - a) providing a substrate [[(1)]],
- b) epitaxially growing a plurality of semiconductor layers on to onto the substrate [[(1)]], which semiconductor layers include the pump radiation source [[(20)]],
- c) forming a window in the plurality of semiconductor layers for the quantum well structure, (11), and
- d) epitaxially growing the quantum well structure [[(11)]] in the window so that the pump radiation source [[(20)]] adjoins the quantum well structure [[(11)]], and
- <u>e)</u> forming wherein a recess [[(10)]] for introducing the pump radiation [[(2)]] into the quantum well structure, the recess being located (11) is formed between the pump radiation source [[(20)]] and the quantum well structure [[(11)]],

wherein the pump radiation source is a pump laser comprising a resonator, and

wherein the quantum well structure is arranged within the resonator of the pump radiation source.

- 26. (Currently Amended) The method as claimed in claim 25, wherein [[in]] step d) further comprises growing semiconductor layers are grown in order to form the quantum well structure [[(11)]], these semiconductor layers in a grow-in region, being at least partially growing grown together in [[the]] a lateral direction with [[the]] a layer sequence of the pump radiation source [[(20)]], and wherein step e) further comprises forming the recess (10) is formed by at least partial removal of the grow-in region [[(19)]].
- 27. (Currently Amended) The method as claimed in claim 25, wherein the recess [[(10)]] is formed by etching, in particular, wet chemical or dry chemical etching.
- 28. (Currently Amended) The method as claimed in claim 25, wherein the recess [[(10)]] is designed in the form of a trench, in particular as an etched trench.
- 29. (Currently Amended) The method as claimed in claim 25, wherein the recess [[(10)]] is filled with a material which transmits the pump radiation.
- 30. (Currently Amended) The method as claimed in claim 29, the recess [[(10)]] is filled with $\underline{\mathbf{a}}$ silicone or a semiconductor material.

- 31. (New) The semiconductor device as claimed in claim 3, wherein at least one of the first and the second side faces includes an angle equal to a Brewster angle with a main direction of emission of the pump radiation source.
- 32. (New) The semiconductor device as claimed in claim 1, wherein the pump radiation source comprises an edge-emitting semiconductor laser, and wherein the semiconductor body has outer side faces forming resonator mirrors.